



**THE
TECHNOLOGY
FOR
SUSTAINABLE
FUTURE**



about us

REVEGO Environmental Solutions and Technologies, develops end-to-end solutions with product development, software systems, digital infrastructure and storage systems for the sector within the scope of environmental policies. It produces Deposit Reverse Vending Machines, Counting & Sorting Machines, Verification Facilities, Mobile Return Station whose system and software are implemented in-house. It operates in its factory with an area of 10.000 m2 with the aim of realizing all processes covering design, software, production, distribution, marketing, assembly and after-sales services in the national and international market.

REVEGO is one of the ÜÇGE Group Companies under which 10 companies operate.

With 48 years of deep-rooted history, ÜÇGE continues its activities as one of the world's major suppliers of retail shelves systems, warehouse racking systems, smart storage, digital system solutions, environmental solutions and a wide range of industrial products.

ÜÇGE Group is moving forward with the goal of creating more value for its industry, its customers and the world for a sustainable future. In this context, as of 2020, it has stepped into R&D, production and software activities in the

field of recycling. Important projects were realized in a short time.

In the second half of 2023, REVEGO was established as a new company specific to its field of activity. All environmental solutions started to be implemented under REVEGO.

REVEGO also aims to use our planet's resources efficiently, to create a sustainable system to support the circular economy and to raise recycling awareness in society with its corporate citizenship approach.

It combines its goals with the vision of creating value for the future.

products

REVEGO, the deposit return machine, which can accept PET, Can and Glass bottles in certain volume ranges, is more than just an indicator of environmental awareness, it offers a solution that optimizes the recycling process.

Stand Alone RVMs



RVG-i10G



Only for
Glass Bottles



RVG-i20



For PET
and Can



RVG-i30



For Glass, PET
and Can

Mobile Return Station

RVG-i100



For Glass, PET and Can



RVG-i10G

Designed for glass bottles within the scope of DRS, it maximizes bottle breakage with minimum footprint, offering higher storage volume.

Height: 1885 mm Width: 750 mm Depth: 955 mm
 Weight: 355 kg Footprint: 0,7 m²

Highlights:

- Only for 0,1-3,0-liter glass bottles
- Easy to use with a 15" touchscreen user friendly interface
- QR code reader for third part mobile applications
- Fast EAN Barcode Reading with 360 Barcode Scanner
- AI-powered Basic Shape Recognition capability
- Real-time weight measurement
- High strength glass crushing unit
- ~600 crushed glass bottles capacity
- Card top up, e-wallet, receipt reimbursement methods



Technical Details

MATERIAL TYPES	Glass Bottles
CONTAINER SIZE	Max 3,0 litres
LOCATION	Internal
WEIGHT	355 kg.
DIGITAL SCREEN	15" touch screen
REWARD SYSTEM	Card Top Up, E-Wallet and Receipt
AUTOMATION	360° Barcode, shape, material and weight sensors
PRODUCTIVITY	40 units per min
CAPACITY	600 Glass Bottles (crushed) (120 lt euro wheelie bin)
COMPACTION	Crushing Units (0,75 Kw)
POWER CONSUMPTION	Idle 61W – Max 1,1 Kw
POWER SUPPLY	230 V, 50 Hz, 13 A
NOISE	<83 db. (Glass)
TEMPERATURE	-10°C to 45°C
CONNECTION	LAN (Ethernet), Mobile

Usage Areas



General Information

- For Glass Bottles
- Fast identification (360° Barcode reading)
- Shape (silhouette) recognition
- Material detection
- Weight measurement
- Capacity, 1 x 1/2 EU PaletCrushing unit
- Full coverage after sales service
- 7/24 remote monitoring

RVG-i20

Designed for PET and Cans within the scope of DRS, it maximizes compressing with minimum footprint, offering higher storage volume.

Height: 1885 mm Width: 750 mm Depth: 955 mm
 Weight: 355 kg Footprint: 0,7 m²

Highlights:

- Only for 0,1-3,0-liter Pet and Cans
- Easy to use with a 15" touchscreen user friendly interface
- QR code reader for third part mobile applications
- Fast EAN Barcode Reading with 360 Barcode Scanner
- AI-powered Basic Shape Recognition capability
- Real-time weight measurement
- High strength pressing unit
- ~ 460 Pet – 800 Can capacity
- Card top up, e-wallet, receipt reimbursement methods



Technical Details

MATERIAL TYPES	Pet Bottles and Cans
CONTAINER SIZE	Max 3,0 litres
LOCATION	Internal
WEIGHT	355 kg.
DIGITAL SCREEN	15" touch screen
REWARD SYSTEM	Card Top Up, E-Wallet and Receipt
AUTOMATION	360° Barcode, shape, material and weight sensors
PRODUCTIVITY	40 units per min
CAPACITY	460 Pet Bottles, 800 Can
COMPACTION	Pressing Units (0,75 Kw)
POWER CONSUMPTION	Idle 61W – Max 1,1 Kw
POWER SUPPLY	230 V, 50 Hz, 13 A
NOISE	<72 db. (Pet/Can)
TEMPERATURE	-10°C to 45°C
CONNECTION	LAN (Ethernet), Mobile

Usage Areas



General Information

- For Pet and Cans
- Fast identification (360° Barcode reading)
- Shape (silhouette) recognition
- Material detection
- Weight measurement
- Capacity, 1 x 1/2 EU Palet Pressing unit
- Full coverage after sales service
- 7/24 remote monitoring

RVG-i30

Designed for Pet Can and Glass bottles within the scope of DRS, it compacts maximum products in minimum space, offering a higher storage volume.

Height: 1885 mm **Width:** 1485 mm **Depth:** 955 mm
Weight: 495 kg **Footprint:** 1,4 m²

Highlights:

- Only for 0,1-3,0-liter pet, can and glass bottles
- Easy to use with a 15" touchscreen user friendly interface
- QR code reader for third part mobile applications
- Fast EAN Barcode Reading with 360 Barcode Scanner
- AI-powered Basic Shape Recognition capability
- Real-time weight measurement
- High strength glass crushing unit
- 460 Pet Bottles, 800 Aluminum Cans (compacted), 400 Glass Bottles (crushed)
- Card top up, e-wallet, receipt reimbursement methods



Technical Details

MATERIAL TYPES	Pet Bottles, Aluminum Cans, Glass Bottles
CONTAINER SIZE	Max 3,0 litres
LOCATION	Internal
WEIGHT	495 kg.
DIGITAL SCREEN	15" touch screen
REWARD SYSTEM	Card Top Up, E-Wallet and Receipt
AUTOMATION	360° Barcode, shape, material and weight sensors
PRODUCTIVITY	40 units per min
CAPACITY	460 Pet Bottles, 800 Aluminum Cans (compacted) 400 Glass Bottles (crushed) (90 lt euro wheelie bin)
COMPACTION	Pressing (0,75 Kw) and Crushing Units (0,75 Kw)
POWER CONSUMPTION	Idle 61W – Max 2,2 Kw
POWER SUPPLY	230 V, 50 Hz, 13 A
NOISE	<75 db. (PET/Can), <85 db. (Glass)
TEMPERATURE	-10°C to 45°C
CONNECTION	LAN (Ethernet), Mobile

Usage Areas



General Information

- For Pet, Can and Glass Deposit containers
- Fast identification (360° Barcode reading)
- Shape (silhouette) recognition
- Metal and material detection
- Weight measurement
- Capacity, 1 x 1/1 EU Palet or 2x 1/2 EU Palet
- Pressing and crushing unit
- Full coverage after sales service
- 7/24 remote monitoring

RVG-i100

Designed for Pet Can and Glass bottles within the scope of DRS, it compacts more than 5000 deposit containers in effective space offering highest storage volume.

Height: 2614 mm
Width: 2430 mm
Depth: 8810 mm

Weight: 8500 kg
Footprint: 56 m²

Highlights:

- High speed Bulk Feeding
- Identification speed is 120 containers per minute
- Modular system
- Mounted on a collection truck
- Electrical feeding lid
- Plug&Play
- 27" touchscreen



Technical Details

PACKAGING TYPE	PET - Can - Glass
HEIGHT (H) X DEPTH (P) X LENGTH (L)	2614 x 8810 x 2430
FOOT PRINT (M2)	56
WEIGHT (KG)	8500
AREA	Indoor - Outdoor
REWARD SYSTEM	Receipt-Mobile wallet-Card application
USER RECOGNITION	Exist
CRUSHER UNIT	Exist
GLASS BREAKER	Exist
POWER OF CRUSHER / BREAKER UNIT (kW)	0,75 kW x 3
DISPLAY (INC)	27" Touch Screen
THERMAL PRINTER	Exist
360 DEGREE BARCODE READER	Exist

SHAPE (SILHOUETTE) RECOGNITION	Exist
WEIGHT MEASUREMENT	Exist
MACHINE IDENTIFICATION SPEED (PRODUCT/MIN)	120*
CONTAINER SIZES	Depend on project design
CAPACITY BY PRODUCT TYPE	Depend on project design
OPERATING TEMPERATURE	Between (-)10C° - (+)40C°
POWER CONSUMPTION	StandBy 61 W - Max 3,5 kW
MAINS	230 V AC- 1 Phase, 50 Hz****
CONNECTION	LAN (Ethernet), Mobile
NOISE	<72 (PET/Can), <83 (Glass)
MAIN SOFTWARE	Exist
(instant reporting, occupancy rate, technical service records)	
OPERATING SYSTEM	Linux



after sales

Installation

RVMs installation service offers seamless integration of Reverse Vending Machines (RVMs) into diverse locations, including supermarkets, public areas, and recycling centers. Our comprehensive service encompasses assessment, installation, configuration, testing, and training. We ensure optimal placement, functionality, and user experience, promoting recycling participation and environmental sustainability.

Repair

RVMs Repair service offers prompt and reliable solutions to ensure optimal performance of Reverse Vending Machines (RVMs). Our skilled technicians diagnose and address issues efficiently, restoring functionality and minimizing downtime. With a focus on quality repairs and customer satisfaction, we keep RVMs operating smoothly, promoting continuous recycling efforts.

Maintenance & Cleaning

RVMs Maintenance & Cleaning service ensures peak performance and hygiene standards for Reverse Vending Machines (RVMs). Our dedicated team conducts regular maintenance checks, including thorough cleaning and sanitization, to uphold operational efficiency and user satisfaction. With a focus on reliability and cleanliness, we ensure that RVMs continue to promote recycling efforts effectively.

electrical collection truck

collection

The eco-friendly solution for efficient recycling collection. Powered by electricity, this innovative vehicle minimizes carbon emissions while maximizing collection capacity. For more information click here...



Route Planning

Software-supported route planning for smart waste collection vehicles used in the collection of RVMs (Reverse Vending Machines) involves optimizing collection routes for maximum efficiency and effectiveness. By leveraging advanced algorithms and real-time data, our system intelligently plans routes, considering factors such as RVM locations, waste volume, traffic conditions, and vehicle capacity.

electrical collection truck

collection

Designed for a sustainable micro transportation...

- Doors opening 90 degrees in both directions, a high seating position and a large ingress zone provide easy access into vehicle.
- You can enjoy silent, tailpipe emission free drive thanks to %100 electric power pack even on a 25% slope at fully loaded.
- Bad Weather? You don't have to compromise on your comfort and safety.
- Bee 1 offers reducing your operational costs by 90% with an affordable initial acquisition price.
- Charge your vehicle in 3.5 hours with nearest 220V household socket.
- 70-150 km electric range covers a daily usage of most customers, however also can be upgraded on your demand.



Range
70-150 km



Top Speed
55 kph



Charge Time
3.5 hours



Payload
350 kg



Load Capacity
1.350 L



Low
Operational
Cost



Charge From
Household
Outlet



100%
Electric



RVG Online / RVM Operating Software

digital tools

RVG Online serves as the backbone of Reverse Vending Machines, managing key functions such as user interaction, transaction processing, and data management. This software ensures seamless operation and reliability, enabling efficient recycling and accurate deposit handling. With user-friendly interfaces and robust backend capabilities, our operating software optimizes RVM performance, enhances user experience, and facilitates effective waste management.



RVG Api's / Application Programming Interfaces

RVG APIs (Application Programming Interfaces) facilitate seamless integration and communication between Reverse Vending Machines and external systems or applications. By providing standardized methods for accessing RVM data and functionality, these APIs enable developers to build custom solutions, such as mobile apps, reporting tools, or backend systems. With RVG APIs, organizations can enhance operational efficiency, automate processes, and unlock new possibilities for recycling management and innovation.



REVEGO Çevresel Çözümler ve Teknolojileri AŞ | Environmental Solutions & Technologies

Işıktepe OSB Kahverengi Cad. No:16 16215 Nilüfer, Bursa TÜRKİYE T: +90 224 280 00 00
| revego.com.tr | sales@revego.com.tr |